


**KAESER**  
KOMPRESORJI

# MOBILAIR

## Program

Mobilni gradbeni kompresorji s svetovno  
znanim SIGMA PROFILOM 

Zmogljivost 1,2 do 34,0 m<sup>3</sup>/min



[www.kaeser.com](http://www.kaeser.com)

MOBILAIR

**KAESER**

# Majhni, vendar močni

z bencinskim motorjem, do 15 bar

Model		M 13	M 15	M 17
Efekt. zmogljivost	(m <sup>3</sup> /min) (cfm)	1,2 - 0,85 42 - 30	1,4* 50*	1,6*-1,0 57* - 35
Obratovalni nadtlak	(bar) (psi)	7 - 13 100 - 190	7* 100*	7* - 15 100* - 220
Tip motorja		Honda GX 630	Honda GX 630	Honda GX 630
Nazivna moč motorja (kW)		15,5	15,5	15,5
Obratovalna teža (kg)		202	202	204
Prostornina rezervoarja za gorivo (l)		20	20	20
Priključki za stisnjen zrak		1 x G½	1 x G½	1 x G½
Hladilnik stisnjenega zraka		opcija	opcija	opcija

\* samo za izvoz izven EU



P-625SL1/14 Pridružujemo si pravico do tehničnih sprememb!

## Alternative

z okolju prijaznim elektromotorjem

Model		M 13 E	M 34 E	M 46 E
Efekt. zmogljivost	(m <sup>3</sup> /min) (cfm)	1,2 - 0,75 42 - 27	3,4 120	4,6 - 3,35 160 - 120
Obratovalni nadtlak	(bar) (psi)	7 - 15 100 - 220	7 100	7 - 10 100 - 145
Tip motorja		ABM 4D112M-2	ATB A160L/-21	Siemens 1LA9 183-2
Nazivna moč motorja (kW)		7,5	22	30
Obratovalna teža (kg)		187	650	720
Varovanje (A)		25	50	63
Priključki za stisnjen zrak		1 x G½	2 x G¾	2 x G¾, 1 x G1
Hladilnik stisnjenega zraka		opcija	opcija	opcija



# Gradbeni kompresorji

s patentirano Anti-Frost-regulacijo



Model	M 20 (PE)	M 27 (PE)	M 31 (PE)	M 36	M 43 (PE)	M 45	M 50 (PE)	M 52
Efekt. zmogljivost (m <sup>3</sup> /min) (cfm)	2,0 71	2,6 92	3,15 - 1,9 110 - 67	3,9 135	4,2 150	4,15 - 4,2 150 - 145	5,0 180	5,2 185
Obratovalni nadtlak (bar) (psi)	7 100	7 100	7 - 14 100 - 200	7 100	7 100	7 - 10 100 - 145	7 100	7 100
Tip motorja	Kubota D 722	Kubota D 1105	Kubota D 1105-T	Deutz TCD 2012 L04	Kubota V 1505-T	Kubota V 2203	Kubota V 1505-T	Kubota V 2203
Nazivna moč motorja (kW)	14,0	17,9	24,1	36,0	30,1	35,4	32,5	35,4
Obratovalna teža (kg)	457	575	580	1145	730	995	735	1225
Prostornina rezervoarja za gorivo (l)	30	40	40	80	80	80	80	105
Priključki za stisnjen zrak	2 x G <sup>3/4</sup>	2 x G <sup>3/4</sup>	2 x G <sup>3/4</sup>	2 x G <sup>3/4</sup> 1 x G1	2 x G <sup>3/4</sup>	2 x G <sup>3/4</sup> 1 x G1	2 x G <sup>3/4</sup> 1 x G1	2 x G <sup>3/4</sup> 1 x G1
Priprava stisnjenega zraka	-	opcija	opcija	opcija	-	opcija	-	opcija
Opcija generator (kVA)	-	-	6,5	13 (serija)	-	8,5	-	8,5



\* samo za izvoz izven EU

## Zmogljivi vsestranski talenti

Stisnjen zrak in še več ...

Model	M 57 Utility	M 57	M 64	M 70	M 80	M 100	M 122
Efekt. zmogljivost (m <sup>3</sup> /min) (cfm)	5,1 - 5,4* 180 - 190 *	5,6 200	6,4 - 5,0 225 - 180	7,0* - 5,4* 250* - 190 *	8,1 - 5,5 285 - 195	10,2 - 6,4 360 - 225	11,1 - 7,3 390 - 260
Obratovalni nadtlak (bar) (psi)	7 100	7 100	7 - 10 100 - 145	7* - 10* 100* - 145*	7 - 14 100 - 200	7 - 14 100 - 200	7 - 14 100 - 200
Tip motorja	Kubota V 2403	Kubota V 2403	Kubota V 2403-T	Kubota V 2003-T	Kubota V 3307 DI-T	Kubota V 3800 DI-T	Deutz TCD 2012 L04
Nazivna moč motorja (kW)	36,0	36,0	43,3	43,3	54,6	71,7	83,0
Obratovalna teža (kg)	960	1225	1230	1230	1480	1480	1865
Prostornina rezervoarja za gorivo (l)	105	105	105	105	150	150	170
Priključki za stisnjen zrak	2 x G <sup>3/4</sup> 1 x G1	2 x G <sup>3/4</sup> 1 x G1	2 x G <sup>3/4</sup> 1 x G1	2 x G <sup>3/4</sup> 1 x G1	2 x G <sup>3/4</sup> 1 x G1½	2 x G <sup>3/4</sup> 1 x G1½	2 x G <sup>3/4</sup> 1 x G1½
Priprava stisnjenega zraka	opcija	-	opcija	opcija	opcija	opcija	opcija
Opcija generator (kVA)	-	-	8,5 / 13	-	8,5 / 13	8,5 / 13	-



\* samo za izvoz izven EU

## Varčni paketi moči

s SIGMA CONTROL MOBIL

Model	M 123	M 135	M 170	M 200	M 250	M 350
Efekt. zmogljivost (m <sup>3</sup> /min) (cfm)	11,4 - 8,1 405 - 285	13,0 - 10,5 460 - 370	17,0 - 11,5 600 - 405	21,2* - 14,5 750* - 515	26,3 - 20,0 930 - 705	34,0 - 24,0 1200 - 850
Obratovalni nadtlak (bar) (psi)	8,6 - 14 125 - 200	10 - 14 145 - 200	8,6 - 14 125 - 200	7* - 14 100* - 200	8,6 - 14 125 - 200	8,6 - 14 125 - 200
Tip motorja	Deutz TCD 2012 L04	Deutz TCD 2013 L04	Deutz TCD 2012 L06	Caterpillar C 6.6 ACERT	Mercedes Benz OM 926 LA	Mercedes Benz OM 501 LA
Nazivna moč motorja (kW)	88	122	128	146	215	265
Obratovalna teža (kg)	1945	2500	2600	3235	3520	6200
Prostornina rezervoarja za gorivo (l)	170	200	200	270	250	650
Priključki za stisnjen zrak	3 x G <sup>3/4</sup> , 1 x G1½	3 x G <sup>3/4</sup> , 1 x G2	3 x G <sup>3/4</sup> , 1 x G2	3 x G <sup>3/4</sup> , 1 x G2	3 x G <sup>3/4</sup> , 1 x G2	2 x G2½ 1 x G1
Priprava stisnjenega zraka	opcija	opcija	opcija	opcija	opcija	opcija
Opcija generator (kVA)	-	15/23	-	-	-	-



\* samo za izvoz izven EU