

KAESER
KOMPRESORJI®



Program MOBILAIR® s skladnostjo CE

Mobilni kompresorji s svetovno priznanim SIGMA PROFILOM ⚙️

Dobavna količina od 1,2 do 48,1 m³/min

www.kaeser.com

Alternativni pogoni

			e-power	
Model			M 13	M 17
Prostorninski tok pri obratovalnem nadtlatku	7 bar	m³/min	1,2	–
	100 psi	cfm	42	
	10 bbarv	m³/min	1,0	–
	145 psi	cfm	35	
	13 bar	m³/min	0,85	–
	175 psi	cfm	30	
	15 bar	m³/min	–	1,0
	200 psi	cfm		35
Tip motorja			Honda GX 630	Honda GX 630
Nazivna moč motorja			kW	15,5
Priprava stisnjenega zraka			○	○



Kompaktne naprave

			e-power					
Model			M 20	M 27	M 30	M 27E	M 31E	M 50E
Prostorninski tok pri obratovalnem nadtlatku	7 bar	m³/min	2,0	2,6	2,9	2,6	3,15	5,0
	100 psi	cfm	71	92	100	92	110	180
	10 bar	m³/min	–	2,1	–	–	2,6	3,8
	145 psi	cfm		74			92	135
	12 bar	m³/min	–	1,9	–	–	2,3	–
	175 psi	cfm		67			81	
	14 bar	m³/min	–	1,6	–	–	1,9	–
	200 psi	cfm		57			67	
Tip motorja			Kubota D722	Kubota D1105	Kubota D1105	Siemens	Siemens	Siemens
Nazivna moč motorja			kW	14,7	18,2	18,2	15	22
Priprava stisnjenega zraka			○	○	○	○	○	○
Opcija generatorja			kVA	–	6,5	–	–	–




Multitalenti

			M 58utility	M 59	M 65	M 82
Prostorninski tok pri obratovalnem nadtlatku	7 bar	m³/min	5,1	5,5	6,6	8,4
	100 psi	cfm	180	195	230	295
	10 bar	m³/min	4,35	4,7	5,6	6,8
	145 psi	cfm	155	165	195	240
	12 bar	m³/min	–	–	–	6,1
	175 psi	cfm				215
	14 bar	m³/min	–	3,8	4,6	5,5
	200 psi	cfm		135	160	195
Tip motorja			Kubota V2403-CR	Hatz 3H50TICD	Kubota V2403CR-T	Kubota V3307-CR-T
Nazivna moč motorja			kW	35,3	43,5	47,9
Priprava stisnjenega zraka			○	○	○	○
Opcija generatorja			kVA	–	8,5/13	–



Paketi moči

Model			M 125		M 171	
Prostorninski tok pri obratovalnem nadtlaku	8,6 bar	m³/min	–		17,0	
	125 psi	cfm			600	
	10 bar	m³/min	11,5	15,5		
	145 psi	cfm	405	550		
	12 bar	m³/min	10,7	13,5		
	175 psi	cfm	380	475		
	14 bar	m³/min	9,7	11,5		
	200 psi	cfm	345	405		
Tip motorja			Deutz TCD 4.1 L04		Deutz TCD 6.1 L06	
Nazivna moč motorja		kW	105		129	
Priprava stisnjenega zraka			○		○	
Opcija generatorja		kVA	13		–	



Veliki kompresorji

Model				M 255		e-power		
						M 250E	M 255E	
Prostorninski tok pri obratovalnem nadtlaku	8,6 bar	m³/min	26,5			25,0	–	
	125 psi	cfm	950			885		
	10 bar	m³/min	24,8			20,4	24,7	
	145 psi	cfm	875			720	875	
	12 bbar	m³/min	–			–	19,9	
	175 psi	cfm					705	
	14 bar	m³/min	19,7			16,2	–	
	200 psi	cfm	695			570		
Tip motorja			Cummins B6,7		Siemens		Siemens	
Nazivna moč motorja			kW		210		132	160
Priprava stisnjenega zraka			○		○		○	

